NSN 4930-01-186-2538

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4930-01-186-2538

| Mounting Type: |
|---|
| Unthreaded hole bottom |
| Mounting Hole Diameter: |
| 0.500 inches |
| Mounting Hole Quantity: |
| 4 |
| Body Length: |
| 6.500 inches |
| Body Height: |
| 24.310 inches |
| Filtration Rating In Microns: |
| 10.0 |
| Distance Between Mounting Hole Centers: |
| 5.000 inches |
| Design Type: |
| Reusable |
| Filtering Element Quantity: |
| 2 |
| Maximum Operating Pressure: |
| 2000.0 pounds per square inch |
| Filtering Media Design: |
| Pleated single filtering media response |
| First Intake Connection Type: |
| Plain face flange top side |
| First Discharge Connection Relationship To Intake Connection: |
| Not identical |
| First Discharge Connection Type: |
| Plain face flange bottom side |
| Distance From Bottom Of Body To Center Of Inlet: |
| 20.180 inches |
| Center To Center Distance Between Connections: |
| 17.180 inches |
| Angle Between Connections: |
| 180.0 degrees |
| First Intake Flange Shape Style: |
| Rectangular w/unthreaded bolt holes |
| First Discharge Flange Shape Style: |
| Rectangular w/unthreaded bolt holes |
| First Intake Flange Face Style: |
| Plain |
| First Discharge Flange Face Style: |

Plain

NSN 4930-01-186-2538 Fluid Filter - Page 2 of 2



| First Intake Flange Thickness: |
|--|
| 3.000 inches |
| First Discharge Flange Thickness: |
| 3.000 inches |
| First Intake Flange Length: |
| 6.500 inches |
| Err Default: |
| Err default |
| First Intake Flange Width: |
| 6.000 inches |
| Err Default: |
| Err default |
| Filtering System For Which Designed: |
| By-pass flow |
| Material: |
| Steel body |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon |
| Style Designator: |
| Offset flow basket strainer w/bolted cover |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A24000 |