NSN 4930-01-423-6542

Hose Reel Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4930-01-423-6542 **Drive Connection Type:** Gear **Current Type:** Dc **Nonsparking Provision:** Not included **Inclosure Type:** Explosion proof **Furnished Items And Quantity:** Includes hand crank assembly **Ambient Temp:** 125.0 degrees fahrenheit Controller: Included **Err Default:** Err default **End Connection Type:** Female tapered pipe threaded **Pressure Capacity:** 125.0 pounds per square inch Clutch: Not included **Installation Location:** Left hand and right hand **Mounting Facility:** Floor Wattage Rating: 499.820 watts **Hose Length Accommodated:** 60.000 feet **Hose Diameter Accommodated:** 2.060 inches **Reel Rim Outside Diameter:** 25.000 inches **Reel Hub Width:** 10.120 inches **Fixed Reel Hose Piping Connection Type:** Swing joint **Motor Switch:** Included **Mounting Plate Width:**

15.750 inches

NSN 4930-01-423-6542

Hose Reel Assembly - Page 2 of 2



Hub Center Line Height Above Base:
14.250 inches
Reel Actuation Method:
Electrical motor
Voltage In Volts:
12.0
Special Features:
2" inlet straight victaulic connection
Media For Which Designed:
Fuel/oil, hydrocarbon
Supplementary Features:
End item is 2330-01-377-9337, semitrailer, tank
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T293-h