

View Online at <https://aerobasegroup.com/nsn/4930-01-496-3543>

**Drive Connection Type:**

Spring wound

**Pressure Capacity:**

1800.0 pounds per square inch

**Clutch:**

Not included

**Hose Length Accommodated:**

60.000 feet

**Hose Diameter Accommodated:**

0.500 inches

**Reel Rim Outside Diameter:**

20.000 inches

**Fixed Reel Hose Piping Connection Type:**

Swing joint

**Mounting Plate Width:**

8.500 inches

**Reel Actuation Method:**

Mechanical spring

**Product Name:**

Series 500 hose reel - no hose

**Special Features:**

Bare reel only, does not include hose; holds of 40 to 50 ft. Of 0.500 in. Inside diameter hose; end connection 0.500 male npt fitting; media - oil, light lubricants, motor oil, automatic transmission fluids, and gear lube; reel inlet 0.500 in. Threaded male npsm; reel outlet swivel union 0.500 in. Threaded female npsm and 0.375 in. Threaded male npt; bearings are oil impregnated porous bronze; wetted parts are carbon steel and nitrile rubber; mounting plate is 8.500 in. By 8.000 in. With four mounting slots, two each on 8.500 in. Sides 6.880 in. On centers and 0.440 in. Wide; length of reel assembly is 25.750 in.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T293-h