

View Online at <https://aerobasegroup.com/nsn/4930-01-496-3543>

Drive Connection Type:

Spring wound

Pressure Capacity:

1800.0 pounds per square inch

Clutch:

Not included

Hose Length Accommodated:

60.000 feet

Hose Diameter Accommodated:

0.500 inches

Reel Rim Outside Diameter:

20.000 inches

Fixed Reel Hose Piping Connection Type:

Swing joint

Mounting Plate Width:

8.500 inches

Reel Actuation Method:

Mechanical spring

Product Name:

Series 500 hose reel - no hose

Special Features:

Bare reel only, does not include hose; holds of 40 to 50 ft. Of 0.500 in. Inside diameter hose; end connection 0.500 male npt fitting; media - oil, light lubricants, motor oil, automatic transmission fluids, and gear lube; reel inlet 0.500 in. Threaded male npsm; reel outlet swivel union 0.500 in. Threaded female npsm and 0.375 in. Threaded male npt; bearings are oil impregnated porous bronze; wetted parts are carbon steel and nitrile rubber; mounting plate is 8.500 in. By 8.000 in. With four mounting slots, two each on 8.500 in. Sides 6.880 in. On centers and 0.440 in. Wide; length of reel assembly is 25.750 in.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T293-h