Trailer Mounted Aircraft Fuel Servicing Unit - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4930-01-617-3365



Wheel Quantity:

Λ	
-	

- Maximum Discharge Flow Rate:
- 12.0 gallons per minute

Tire Type:

Pneumatic

Wheel Diameter:

20.5 inches

Aircraft Type For Which Designed:

Fighter

Fuel Filter:

Included

Pressure Fueling System Type For Which Designed:

Any acceptable

Fueling Hose Reel:

Included

Single Point Fueling Nozzle Maximum Discharge Flow Rate:

10.0 gallons per minute

Fuel Meter:

Included

Trailer Material:

Steel, corrosion resisting

Trailer Pintle Towing Assembly:

Not included

Trailer Steering Type:

Nonsteering type

Trailerlength:

Between 156.0 inches and 221.0 inches

Trailerwidth:

77.0 inches

Trailerheight:

Between 62.00 inches and 72.00 inches

Product Name:

Handifueler

Special Features:

Age600s gp12vdc, 600 gallon aircraft ground equipment handifueler service cart, with secondary containment, and fillrite pump/meter. The handifueler consists of an inner tank assembly and an outer tank. Fuel servicing is accomplished with a 12 volt dc pump, fuel meter, fuel filter, and a plumbing system that allows for the direction of fuel into or out of the inner tank assembly based on the method of fuel service selected. The handifueler is also designed to allow for non fuel related serving of aircraft ground equipment.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

NSN 4930-01-617-3365

Trailer Mounted Aircraft Fuel Servicing Unit - Page 2 of 2

Fiig: T293-a

