

View Online at <https://aerobasegroup.com/nsn/4931-00-330-3185>

**Width:**

13.000 inches and 8.500 inches

**Length:**

17.000 inches and 17.250 inches

**Ac Voltage Rating:**

115.000 volts

**Dc Voltage Rating:**

-200.0 volts and 200.0 volts

**Frequency Rating:**

60.000 hertz

**Major Components:**

Cable; cable; cable; cable; cable; cable; rack assembly

**Accessory Component Quantity:**

1 and 1 and 1 and 1 and 3 and 1 and 1

**Accessory Controlling Agency:**

Buord; buord; buord; buord; buord; buord; buord

**Accessory Identifying Number:**

1401271 drawing no. And 1401272 drawing no. And 1401273 drawing no. And 1401274 drawing no. And 1401275 drawing no. And 1401276 drawing no. And 1468570 drawing no.

**Internal Battery Accommodation:**

Not included

**Material And Location:**

Aluminum carrying case and aluminum carrying case

**Inclosure Feature:**

Multiple item w/carrying case

**Test Type For Which Designed:**

Measurement of voltage and resistance; observe voltage wave forms; test components

**Operating Test Capability:**

Meter unit assembly, range minus 40 to 0 to plus 40 v dc, range 0.0005 to 0.005 rms v ac, 0.005 to 0.05 rms v ac, 0.05 to 0.5 rms v ac, 0.5 to 5 rms v ac, 5 to 50 rms v ac, 50 to 500 rms v ac, range 0 to minus 1.2/12/60/300/1200 v dc, 0 to plus 1.2/12/60/300/1200 v dc, 0 to 1.2/12/60/300/1200 v ac, resistance range 0 to 1000 ohms/100000 ohms/1 meg/10 meg/1000 meg dc; oscilloscope unit, deflection sensitivity through amplifier 0.075 rms v per in., vertical and horizontal frequency response 1 to 50000 cps on x axis 5 cps to 2 mc on y axis, saw-tooth sweep range 3 to 50000, cps sine wave sweep 60 cps, phase shift indicator range 0 to 360 deg

**Phase:**

Single

**Height:**

6.750 inches and 10.000 inches

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T228-a