

View Online at <https://aerobasegroup.com/nsn/4935-00-073-8744>

**Ac Voltage Rating:**

115.0 volts

**Frequency Rating:**

Between 60.0 hertz and 400.0 hertz

**End Application:**

F-4 phantom

**Electrical Power Source Relationship:**

Operating

**Inclosure Feature:**

Multiple item w/housing

**Test Type For Which Designed:**

Signal inputs

**Special Features:**

Manual testing; indicator types: scope, meters, gages, lamps; c/o modulation and control panel; dc power panel; a-c power panel; feedthrough panel; hydraulics pump (browne and sharp); oscilloscope (hp130c); heat exchange (fairchild 1024); power meter (hp130cr); ac vtvm (ballantine 3108); power meter (model hp 430cr); input power panel; blower panel; hydraulic gage panel; 400 cps monitor and control assembly; weighing scale (howe 5603); power supply; blower (roton 2591-1032)

**Functional Description:**

Provides facilities for final test of radar transmitter t-888/apa-157. Provides modulation, control signals, and necessary operating power to the transmitter under test. Test set also contains a cooling system to supply os-45 coolant to uut

**Reference Data And Literature:**

T.O. 33d5-12-163-11

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T228-a