

View Online at <https://aerobasegroup.com/nsn/4935-00-732-7813>

Thread Class:

2b first end

Thread Direction:

Right-hand both ends

Thread Length:

0.188 inches second end

Overall Length:

7.308 inches

Thread Depth:

0.313 inches first end

Tip Length:

0.250 inches second end

Shank Outside Diameter:

0.313 inches second end

Tongue Thickness:

0.094 inches first end

Core Material:

Steel, carbon

Screw Thread Series Designator:

Unef first end

Core Surface Treatment:

Any acceptable

Core Diameter:

0.147 inches

Thread Location:

Internal first end

End Type:

Round, flatted two sides, external first end

End Connection Type:

Shouldered ferrule both ends

Tongue Length:

0.172 inches first end

Casing Material:

Steel, carbon

Cross Section Size And Location:

0.375 inches diameter second end

Torsional Deflection Rating:

0.7 degrees per in.-lb winding and 0.8 degrees in.-lb unwinding torsional deflection

Casing Surface Treatment:

Any acceptable

Casing Outside Diameter:

0.234 inches

Casing Protective Device Type:

Braided wire shield

Swivel End:

Not provided both ends

Enddiameter:

0.750 inches first end

Lubrication Fitting:

Not provided both ends

Corelength:

6.922 inches

Core Rotation Direction:

Clockwise

Core Removability:

Nonremovable

Minimum Operating Radius:

3.000 inches

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T246-e