

View Online at <https://aerobasegroup.com/nsn/4935-00-732-7813>

**Thread Class:**

2b first end

**Thread Direction:**

Right-hand both ends

**Thread Length:**

0.188 inches second end

**Overall Length:**

7.308 inches

**Thread Depth:**

0.313 inches first end

**Tip Length:**

0.250 inches second end

**Shank Outside Diameter:**

0.313 inches second end

**Tongue Thickness:**

0.094 inches first end

**Core Material:**

Steel, carbon

**Screw Thread Series Designator:**

Unef first end

**Core Surface Treatment:**

Any acceptable

**Core Diameter:**

0.147 inches

**Thread Location:**

Internal first end

**End Type:**

Round, flattened two sides, external first end

**End Connection Type:**

Shouldered ferrule both ends

**Tongue Length:**

0.172 inches first end

**Casing Material:**

Steel, carbon

**Cross Section Size And Location:**

0.375 inches diameter second end

**Torsional Deflection Rating:**

0.7 degrees per in.-lb winding and 0.8 degrees in.-lb unwindingtorsional deflection

**Casing Surface Treatment:**

Any acceptable

**Casing Outside Diameter:**

0.234 inches

**Casing Protective Device Type:**

Braided wire shield

**Swivel End:**

Not provided both ends

**Enddiameter:**

0.750 inches first end

**Lubrication Fitting:**

Not provided both ends

**Corelength:**

6.922 inches

**Core Rotation Direction:**

Clockwise

**Core Removability:**

Nonremovable

**Minimum Operating Radius:**

3.000 inches

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T246-e