

View Online at <https://aerobasegroup.com/nsn/4940-00-249-7315>

**Mounting Type:**

Trailer

**Cylinder Quantity:**

1

**Wheel Quantity:**

4

**Tire Size:**

Any acceptable

**Hazard Protection Feature:**

Nonmagnetic

**Furnished Items And Quantity:**

Spray gun with double wand construction will switch from wash to rinse with a switch or valve

**Tire Type:**

Pneumatic

**Hose Length:**

25.000 feet

**Wheel Arrangement Style:**

Front and rear, single

**Heating Method:**

Diesel oil or jet fuel

**Pump Capacity:**

240.0 gallons per hour

**Cooling Method:**

Liquid

**Steam Generator:**

Included

**Hose Connection Quantity:**

1

**Outside Steam Source:**

Not required

**Steam Pressure Rating:**

Between 200.0 pounds per square inch and 400.0 pounds per square inch

**Outside Water Source:**

Not required

**Maximum Cleaning Solution Jet Pressure Rating:**

400.0 pounds per square inch

**Cleaning Solution Maximum Discharge Rate:**

400.0 gallons per hour

**Maximum Liquid Jet Pressure Rating:**

400.0 pounds per square inch

**Maximum Liquid Discharge Rate:**

400.0 gallons per hour

**Cleaning Gun Quantity:**

1

**Nozzle Adjustability:**

Adjustable

**Stored Material:**

Fuel and soap concentrate and water

**Retractable Support Feature:**

Not included

**Voltage In Volts:**

208.0

**Phase:**

Three

**Special Features:**

Max noise 85 db at 25 ft

**Frequency In Hertz:**

60.0

**Functional Description:**

Cleans airplanes and support equipment, requires 208v. Power supply

**Relationship To Similar Equipment:**

Replaces items provided under mil-c-4036 style 1

**Special Test Features:**

Must meet performance specification mil-prf-32032

**Supplementary Features:**

Hose length also 200 ft

**Specification Data:**

81349mil-prf32032 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T276-g

**Mil-std (military Standard):**

Mil-prf-32032 spec.