

View Online at <https://aerobasegroup.com/nsn/4940-00-249-7315>

Mounting Type:

Trailer

Cylinder Quantity:

1

Wheel Quantity:

4

Tire Size:

Any acceptable

Hazard Protection Feature:

Nonmagnetic

Furnished Items And Quantity:

Spray gun with double wand construction will switch from wash to rinse with a switch or valve

Tire Type:

Pneumatic

Hose Length:

25.000 feet

Wheel Arrangement Style:

Front and rear, single

Heating Method:

Diesel oil or jet fuel

Pump Capacity:

240.0 gallons per hour

Cooling Method:

Liquid

Steam Generator:

Included

Hose Connection Quantity:

1

Outside Steam Source:

Not required

Steam Pressure Rating:

Between 200.0 pounds per square inch and 400.0 pounds per square inch

Outside Water Source:

Not required

Maximum Cleaning Solution Jet Pressure Rating:

400.0 pounds per square inch

Cleaning Solution Maximum Discharge Rate:

400.0 gallons per hour

Maximum Liquid Jet Pressure Rating:

400.0 pounds per square inch

Maximum Liquid Discharge Rate:

400.0 gallons per hour

Cleaning Gun Quantity:

1

Nozzle Adjustability:

Adjustable

Stored Material:

Fuel and soap concentrate and water

Retractable Support Feature:

Not included

Voltage In Volts:

208.0

Phase:

Three

Special Features:

Max noise 85 db at 25 ft

Frequency In Hertz:

60.0

Functional Description:

Cleans airplanes and support equipment, requires 208v. Power supply

Relationship To Similar Equipment:

Replaces items provided under mil-c-4036 style 1

Special Test Features:

Must meet performance specification mil-prf-32032

Supplementary Features:

Hose length also 200 ft

Specification Data:

81349mil-prf32032 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T276-g

Mil-std (military Standard):

Mil-prf-32032 spec.