

View Online at <https://aerobasegroup.com/nsn/4940-00-396-1660>

Mounting Type:

Trailer

Cylinder Quantity:

1

Pump Quantity:

1

Wheel Quantity:

4

Tire Size:

Any acceptable

Hazard Protection Feature:

Nonmagnetic

Furnished Items And Quantity:

Hose, acid 1; hose, rinse, 25 ft 1; hose, rinse, 50 ft 1; hose, suction 1; hose, vapor cleaning, 25 ft 1; hose, vapor cleaning, 50 ft 1; hose, water inlet 1; gun, rinse 1; gun, vapor 1; rope, engine starting 1; nozzle, flat, 2 in. 1; nozzle, flat, 4 in. 1; nozzle, round 1; wrench, check valve cap 1

Tire Type:

Pneumatic

Power Source:

Gasoline engine

Capacity:

1.0 gallons

Hose Length:

Between 25.000 feet and 50.000 feet

Wheel Arrangement Style:

Front and rear, single

Heating Method:

Gas or oil

Pump Capacity:

275.0 gallons per hour

Cooling Method:

Air

Steam Generator:

Included

Hose Connection Quantity:

2

Outside Steam Source:

Not required

Outside Water Source:

Not required

Maximum Cleaning Solution Jet Pressure Rating:

90.0 pounds per square inch

Cleaning Solution Maximum Discharge Rate:

150.0 gallons per hour

Maximum Liquid Jet Pressure Rating:

150.0 pounds per square inch

Maximum Liquid Discharge Rate:

275.0 gallons per hour

Cleaning Gun Quantity:

2

Nozzle Adjustability:

Nonadjustable

Storage Tank Quantity:

4

Stored Material:

Fuel and soap concentrate and water

Retractable Support Feature:

Not included

Power Source Horsepower Rating:

3.5

Quantity:

1

Specification Or Standard:

1 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T276-g