

View Online at <https://aerobasegroup.com/nsn/4940-01-357-7962>

Mounting Type:

Trailer or wheel

End Application:

Multi-application

Wheel Quantity:

4

Tire Size:

6.70-15

Tire Type:

Pneumatic

Capacity:

525.0 gallons and 55.0 gallons

Wheel Arrangement Style:

Middle tandem, single

Wheel Diameter:

15.000 inches

Steam Generator:

Included

Outside Steam Source:

Not required

Outside Water Source:

Not required

Maximum Cleaning Solution Jet Pressure Rating:

3000.0 pounds per square inch

Cleaning Solution Maximum Discharge Rate:

300.0 gallons per hour

Maximum Liquid Jet Pressure Rating:

3000.0 pounds per square inch

Maximum Liquid Discharge Rate:

300.0 gallons per hour

Storage Tank Quantity:

2

Stored Material:

Water and soap

Retractable Support Feature:

Not included

Special Features:

Gasoline engine hp: 18; starter: electric std; fuel tank cap.: 10 gal; electrical control: 2000 w, 115 vac, belt driven generator supplies burner and aux 115 vac outlet on an engine systems; frame: structural steel frame comprised of welded 3 in. And 4 in. Channel; built in wand holsters; has a lockable full access door and protects pumps, engine, battert, generator, and controls; heavy duty leaf spring suspension; 200 ft wire-braid hose with quick disconnect fittings; discharge soap injection using precision metering valve controlled at the spray wand; axle: 2; hitch coupler ball size 2.000 in.; dim. 181 in. Lg; 92 in. W; 76 in. H; weight: 2200/6900 lbs

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

T276-g