

View Online at <https://aerobasegroup.com/nsn/4940-01-364-0300>

**Mounting Type:**

Trailer

**Cylinder Quantity:**

1

**Pump Quantity:**

1

**Wheel Quantity:**

4

**Tire Size:**

Any acceptable

**Hazard Protection Feature:**

Nonmagnetic

**Tire Type:**

Pneumatic

**Power Source:**

Gasoline engine

**Capacity:**

5.0 gallons and 100.0 gallons

**Hose Length:**

25.000 feet

**Wheel Arrangement Style:**

Front and rear, single

**Heating Method:**

Gas or gasoline

**Pump Capacity:**

275.0 gallons per hour

**Cooling Method:**

Air

**Steam Generator:**

Included

**Hose Connection Quantity:**

2

**Outside Steam Source:**

Not required

**Outside Water Source:**

Not required

**Maximum Cleaning Solution Jet Pressure Rating:**

90.0 pounds per square inch

**Cleaning Solution Maximum Discharge Rate:**

150.0 gallons per hour

**Maximum Liquid Jet Pressure Rating:**

150.0 pounds per square inch

**Maximum Liquid Discharge Rate:**

275.0 gallons per hour

**Cleaning Gun Quantity:**

2

**Nozzle Adjustability:**

Nonadjustable

**Storage Tank Quantity:**

4

**Stored Material:**

Fuel and soap concentrate

**Retractable Support Feature:**

Not included

**Power Source Horsepower Rating:**

3.5

**Quantity:**

1

**Supplementary Features:**

Hose lg also 50.0 ft; storage tank at 15.0 and one at 1.0; stored material also water

**Specification Or Standard:**

1 style

**Fsc Application Data:**

Multi acft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T276-g

**Mil-std (military Standard):**

Mil-prf-32032 spec.