

View Online at <https://aerobasegroup.com/nsn/4940-01-364-5528>

Overall Height:

10.166 feet

Overall Width:

16.000 feet

Current Type:

Ac

Horsepower Rating:

3.0

Explosion Proof Feature:

Not included

Fan Motor Horsepower Rating:

7.5

Fan Motor Current Type:

Ac

Fan Motor Voltage In Volts:

230.0

Fan Motor Phase:

Three

Safety Fire Curtain:

Not included

Exhaust Fan:

Included

Fan Motor Frequency In Hertz:

60.0

Fan Motor Explosion Proof Feature:

Not included

Err Default:

Err default

Phase:

Three

Special Features:

Recirculating pump unit which c/o 1 pump with 128 gpm capacity, 1-3hp motor (230 v, 60 hz, 3 phase), and 1 pump coupling guard; exhaust fan unit c/o 1-42 in. Dia. Double ring exhaust fan, 1- 7.5 hp motor (230 v, 60 hz, 3 phase), fan capacity: 19500 cfm @ 1.15 static pressure, calculated face velocity: 153 fpm through empty booth; exhaust stack c/o 1-5 ft. By 42 in. Diameter spiral stack with door, 2-5 ft. By 42 in. Dia. Spiral stack, 1-pitched roof flange, 1-combination auto damper and canopy with connector ring; ; misc items c/o 8-55 gallon drums of oil, 1 draft gauge, 1-heat detector device, 1-7.5 starter motor and disconnect, 1-3 hp starter motor with disconnect, 2-push button stations

Frequency In Hertz:

60.0

Functional Description:

Used to filter paint particles from air during spray paint operations; uses oil bath as opposed to water or dry filter methods

Supplementary Features:

5 ft. 2 in. Deep; appx. Wght 12, 100 lbs; arranged for top exhaust

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

T276-s