NSN 4940-01-364-5528

Spraying Booth - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4940-01-364-5528

Overall Height:
10.166 feet
Overall Width:
16.000 feet
Current Type:
Ac
Horsepower Rating:
3.0
Explosion Proof Feature:
Not included
Fan Motor Horsepower Rating:
7.5
Fan Motor Current Type:
Ac
Fan Motor Voltage In Volts:
230.0
Fan Motor Phase:
Three
Safety Fire Curtain:
Not included
Exhaust Fan:
Included
Fan Motor Frequency In Hertz:
60.0
Fan Motor Explosion Proof Feature:
Not included
Err Default:
Err default
Phase:
Three
Special Features:
Recirrulating pump unit which c/o 1 pump with 128 gpm capacity, 1-3hp motor (230 v, 60 hz, 3 phase), and 1 pump coupling guard; exhaus
fan unit c/o 1-42 in. Dia. Double ring exhaust fan, 1- 7.5 hp motor (230 v, 60 hz, 3 phase), fan capacity: 19500 cfm @ 1.15 static pressure,
calculated face velocity: 153 fpm through empty booth; exhaust stack c/o 1-5 ft. By 42 in. Diameter spiral stack with door, 2-5 ft. By 42 in.
Dia. Spiral stack, 1-pitched roof flange, 1-combination auto damper and canopy with connector ring; ; misc items c/o 8-55 gallon drums of
oil, 1 draft gauge, 1-heat detector device, 1-7.5 starter motor and disconnect, 1-3 hp starter motor with disconnect, 2-push button stations
Frequency In Hertz:
60.0
Functional Description:
Used to filter paint particles from air during spray paint operations; uses oil bath as opposed to water or dry filter methods
Supplementary Features:

.....

Shelf Life:

N/a

5 ft. 2 in. Deep; appx. Wght 12, 100 lbs; arranged for top exhaust

NSN 4940-01-364-5528

Spraying Booth - Page 2 of 2



Demilitarization:

No

Fiig:

T276-s