## NSN 5110-01-606-4523

Pipe Cutter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5110-01-606-4523

| Hazard Protection Feature:  |
|---|
| Nonsparking   |
| Design Type:  |
| 1 cutter  |
| Operation Method:   |
| Powered   |
| Feed Type:  |
| Any acceptable  |
| Pipe Size Accommodated:   |
| Between 2.500 inches and 8.000 inches   |
| Beveling/grooving Knife:  |
| Not provided  |
| Err Default:  |
| Err default   |
| Product Name:   |
| Model 258 power pipe cutter   |
| Special Features:   |
| Cuts 2.5 to 8.0 inch schedule 10/40 steel pipe, galvanized pipe, rigid contuit, etc.Powered by rigid no.700 power drive (not                |
| included).Displacement cutter provides square cuts.Operator controls feeding rate by pumping the hydraulic foot pump throughout the         |
| operation. Square cut 21 foot nipple lengths of pipe. Cuts by displacing, no abrasive dust, dangerous sparks, or open flame. Weight: 105.0  |
| pounds.Standard equipment: one (1): ridgid 774 square drive adapter; one (1): 8.5 inch hd cutter wheel assembly; one (1): hydraulic ram and |
| foot pump; two (2): 2.5 inch to 12.0 inch ball transfer pipe supports   |
| Type/model Designation:   |
| 258   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| T294-w  |
|   |
|   |