## NSN 5120-01-399-9012

Torque Wrench - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5120-01-399-9012

| 10.000 inches  Furnished Items: Case  Torque Indicating Mechanism: Dial  Torque Capacity: Between 0.0 meter-newton and 10.0 meter-newton and 0.0 inch-pounds and 90.0 inch-pounds  Torque Scale Graduation: |
|---|
| Case Torque Indicating Mechanism: Dial Torque Capacity: Between 0.0 meter-newton and 10.0 meter-newton and 0.0 inch-pounds and 90.0 inch-pounds   |
| Torque Indicating Mechanism:  Dial  Torque Capacity:  Between 0.0 meter-newton and 10.0 meter-newton and 0.0 inch-pounds and 90.0 inch-pounds   |
| Dial  Torque Capacity:  Between 0.0 meter-newton and 10.0 meter-newton and 0.0 inch-pounds and 90.0 inch-pounds   |
| Torque Capacity:  Between 0.0 meter-newton and 10.0 meter-newton and 0.0 inch-pounds and 90.0 inch-pounds   |
| Between 0.0 meter-newton and 10.0 meter-newton and 0.0 inch-pounds and 90.0 inch-pounds   |
|   |
| Torque Scale Graduation:  |
|   |
| 0.20 meter-newton   |
| Torque Signal Method:   |
| Dial indicator  |
| Drive Surface Size:   |
| 0.250 inches single end   |
| Drive End Shape:  |
| Square single end external  |
| Special Features:   |
| Dual scale; 1 in-lb graduations   |
| Material:   |
| Steel   |
| Surface Treatment:  |
| Chromium  |
| Style Designator:   |
| Rigid frame end drive   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A102a0  |
|   |