NSN 5130-01-397-9005

Portable Electric Drill - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5130-01-397-9005

Speed Adjustments: Variable speed Overall Length: 10.203 inches Current Type: Ac Atternating Current Rating In Amps: 4.0 Frequency Rating: 60.0 hertz Accessory Components And Quantity: Chuck key and chuck key holder Handle Style: Pistol grip handle Size Designator: 0.250 inches Voltage Rating: 120.000 volts Cord Length: 8.000 feet Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Sheft Life: Na Va
Overall Length:10.203 inchesCurrent Type:AcAternating Current Rating In Amps:4.0Frequency Rating:60.0 hertzAccessory Components And Quantity:Chuck key and chuck key holderHandle Style:Pistol grip handleSize Designator:0.250 inchesVoltage Rating:120.000 voltsCord Length:8.000 feetDrive End Type:Keyed jaw chuckNotoad Speed In Rpm:400.0Drive For Which Designed:StraightPlug Connector Type:StraightPuscer Sprovided:ReversiblePhase:SingleSpecial Features:3/8-24 spindle threadShelf Life:NaUnit Of Measure:
10.203 inches Current Type: Ac Ac Atternating Current Rating In Ampe: 4.0 Frequency Rating: 60.0 hertz Accessory Components And Quantity: Chuck key and chuck key holder Handle Style: Pistol grip handle Size Designator: 0.250 inches Voltage Rating: 120.000 volts Cord Length: 8.000 tolts Cord Length: 8.000 tolts No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: Na
Current Type: Ac Aternating Current Rating In Amps: 4.0 Frequency Rating: 60.0 hertz Accessory Components And Quantity: Chuck key and chuck key holder Handle Style: Pistol grip handle Size Designator: 0.250 inches Voltage Rating: 120.000 volts Cord Length: 8.000 tel Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: Na Unit Of Measure:
Ac Alternating Current Rating In Amps: 4.0 Frequency Rating: 60.0 hertz Accessory Components And Quantity: Chuck key and chuck key holder Handle Style: Pistol grip handle Size Designator: 0.250 inches Voltage Rating: 120.000 volts Cord Length: 8.000 feet Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Alternating Current Rating In Amps: 4.0 Frequency Rating: 60.0 hertz Accessory Components And Quantity: Chuck key and chuck key holder Handle Style: Pistol grip handle Size Designator: 0.250 inches Voltage Rating: 120.000 volts Cord Length: 8.000 feet Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
4.0 Frequency Rating: 60.0 hertz Accessory Components And Quantity: Chuck key and chuck key holder Handle Style: Pistol grip handle Size Designator: 0.250 inches Voltage Rating: 120.000 volts Cord Length: 8.000 feet Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: Na
Frequency Rating: 60.0 hertz Accessory Components And Quantity: Chuck key and chuck key holder Handle Style: Pistol grip handle Size Designator: 0.250 inches Voltage Rating: 120.000 volts Cord Length: 8.000 feet Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
60.0 hertz Accessory Components And Quantity: Chuck key and chuck key holder Handle Style: Pistol grip handle Size Designator: 0.250 inches Voltage Rating: 120.000 volts Cord Length: 8.000 feet Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Accessory Components And Quantity: Chuck key and chuck key holder Handle Style: Pistol grip handle Size Designator: 0.250 inches Voltage Rating: 120.000 volts Cord Length: 8.000 feet Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Chuck key and chuck key holder Handle Style: Pistol grip handle Size Designator: 0.250 inches Voltage Rating: 120.000 volts Cord Length: 8.000 feet Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Handle Style: Pistol grip handle Size Designator: 0.250 inches Voltage Rating: 120.000 volts Cord Length: 8.000 feet Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Pistol grip handle Size Designator: 0.250 inches Voltage Rating: 120.000 volts Cord Length: 120.000 volts Cord Length: 8.000 feet Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Size Designator: 0.250 inches Voltage Rating: 120.000 volts Cord Length: 8.000 feet Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure: -
0.250 inches Voltage Rating: 120.000 volts Cord Length: 8.000 feet Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Voltage Rating: 120.000 volts Cord Length: 8.000 feet Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
120.000 volts Cord Length: 8.000 feet Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Cord Length: 8.000 feet 8.000 feet Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
8.000 feet Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Drive End Type: Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Keyed jaw chuck No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
No Load Speed In Rpm: 4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
4000.0 Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Drive For Which Designed: Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure: -
Straight Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Plug Connector Type: 3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
3-prong Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Features Provided: Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Reversible Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Phase: Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Single Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Special Features: 3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
3/8-24 spindle thread Shelf Life: N/a Unit Of Measure:
Shelf Life: N/a Unit Of Measure:
N/a Unit Of Measure:
Unit Of Measure:
Demilitarization:
No
Fiig:
A530z0