

View Online at <https://aerobasegroup.com/nsn/5220-01-047-5663>

Special Features:

Gage, inside roller; consists of 1 base 0.250 in. Thk, 12.000 in. By 14.000 in. Hrs.; 1 front; 1 guide; gusset 4 ea; 1 gage mount, 0.125 in. Thk, 3.000 in. Lg. By 6.000 in. H, hrs.; 1 gage mount 0.375 in. Thk, 2.000 in. Lg, by 3.000 in.H, hrs; 2 ea v guide 0.250 in. Thk, 2.000 in. By 2.000 in.; 1 ea v guide 0.250 in. By 2.000 in.; 1 ea v guide 0.250 in.By 3.000 in. By 7.000 in.; 1 ea lock plate; 2 ea t handle 0.250 in. Diameter by 8.000 in. Lg, hrs; 3 hex nut stl; 1 ea t handle 0.250 in. Diameter by 5.000 in.. Lg, hrs; 1 ea adapter 0.250 in. Thk, 0.500 in. Lg, 3.000 in.; 1 ea adapter 0.500 in. Diameter by 1.000 in.Lg; 3 ea am, std hex soc scr; 2 ea mach scr; 2 guard; 4 ea am. Standard cap scr soc; 4 ea no. 6 washer flat; rnd magnetic rod; 2 ea am standard cap scr soc hd w/nuts; 7 ea am standard plain washer; 1 ea gage ea graduation 0.001 in., total range 2.000 in.; 1 ea am standard cap scr hd w/nuts; 1 ea standard cap scr soc; 2 ea machine scr rnd hd stl

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T303-b