NSN 5305-00-001-4874



Shoulder Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-00-001-4874 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.395 inches and 0.415 inches **Fastener Length:** Between 0.504 inches and 0.514 inches **Head Style:** Hexagon **Head Height:** Between 0.052 inches and 0.072 inches Width Between Flats: 0.219 inches **Shoulder Diameter:** 0.135 inches first shoulder and 0.145 inches first shoulder **Shoulder Length:** 0.099 inches first shoulder and 0.109 inches first shoulder **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Shoulder Shape:** Round first shoulder Material: Copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 377 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Fiig:

No

A003b0

Demilitarization: