NSN 5305-00-001-6359

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-001-6359

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.172 inches and 0.266 inches
Fastener Length:
Between 0.234 inches and 0.266 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.218 inches and 0.226 inches
Head Height:
Between 0.134 inches and 0.138 inches
Locking Feature:
Pellet locking feature
Internal Drive Style:
Hexagon
Thread Diameter:
0.138 inches
Width Across Flats:
Between 0.109 inches and 0.111 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Material:
Steel uns k03104 fastener
Material Specification:
Astma574 assn standard single material response fastener
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 3 federal specification single treatment response
Thread Series Designator:
Unrc
Specification Data:

80205-nas1352 professional/industrial association standard

NSN 5305-00-001-6359

Socket Head Cap Screw - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0