NSN 5305-00-001-9781



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-001-9781 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.381 inches and 0.431 inches **Fastener Length:** Between 0.829 inches and 0.859 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.332 inches and 0.387 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: Between 248.0 brinell standard and 341.0 brinell standard **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5732 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Shank Surface Finish:** 63.0 microinches **Thread Series Designator:** Unf Shelf Life:

N/a **Unit Of Measure: Demilitarization:** No

NSN 5305-00-001-9781Machine Screw - Page 2 of 2



Fiig:

A500d0