

View Online at <https://aerobasegroup.com/nsn/5305-00-001-9809>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.193 inches and 0.228 inches

Fastener Length:

Between 0.484 inches and 0.499 inches

Head Style:

Pan

Head Diameter:

Between 0.256 inches and 0.270 inches

Head Height:

Between 0.087 inches and 0.097 inches

First Diameter From Head:

0.100 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.271 inches and 0.291 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 304l or steel comp 316l or steel comp 302 or steel comp 347 or steel comp 321 or steel comp 317 or steel comp 316 or steel comp 310 or steel comp 309 or steel comp 305 or steel comp 304 or steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

Material Specification:

Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-s-763 federal specification 7th material response or qq-s-763 federal specification 8th material response or qq-s-763 federal specification 9th material response or qq-s-763 federal specification 10th material response or qq-s-763 federal specification 11th material response or 66 assn standard 12th material response or 66 assn standard 13th material response or 66 assn standard 14th material response or 66 assn standard 15th material response or 66 assn standard 16th material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Uinc

Demilitarization:

No

Fig:

A003b0