NSN 5305-00-003-1687

Machine Screw - Page 1 of 1

No Fiig: A500d0



View Online at https://aerobasegroup.com/nsn/5305-00-003-1687 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.069 inches and 0.107 inches **Fastener Length:** Between 0.094 inches and 0.125 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.099 inches and 0.119 inches **Head Height:** Between 0.018 inches and 0.025 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.060 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 **Thread Series Designator:** Unf **Specification Or Standard:** 3 type and 2c style Shelf Life: N/a **Unit Of Measure:** Demilitarization: