NSN 5305-00-003-4353

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-003-4353 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.100 inches and 0.105 inches **Fastener Length:** 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** 0.187 inches **Head Height:** 0.105 inches **First Diameter From Head:** Between 0.078 inches and 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.270 inches and 0.275 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 4140 **Material Specification:** Mil-s-5626 cond c4 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-003-4353

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.