Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-003-4353

-	
	Thread Class:
-	
	Fhread Direction:
	Right-hand
	Fhread Length:
	Between 0.100 inches and 0.105 inches
	Fastener Length:
	0.375 inches
	lead Style:
	Flat chamfer
	lead Diameter:
	0.187 inches
	lead Height:
	0.105 inches
	First Diameter From Head:
	Between 0.078 inches and 0.080 inches
	Distance From Largest Bearing Surface Of Head To End Of First Diameter:
	Between 0.270 inches and 0.275 inches
	nternal Drive Style:
	Slot
	Thread Diameter:
	0.112 inches
T	Fhready Qty Per Inch (tpi):
4	40
Ν	Min. Tensile Strength (psi):
1	60000 pounds per square inch
E	Externally Relieved Body Diameter Quantity:
1	
Ν	Material:
S	Steel comp 4140
N	Material Specification:
Ν	Mil-s-5626 cond c4 military specification single material response
S	Surface Treatment:
C	Cadmium
S	Surface Treatment Specification:
C	Qq-p-416 type 2 cl 2 federal specification single treatment response
T	Thread Series Designator:
ι	Jnc
S	Shelf Life:
٨	N/a
ι	Jnit Of Measure:
_	<u>-</u>

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.