NSN 5305-00-003-8045

Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-003-8045

Thread Class: 2a Thread Direction: Right-hand Thread Length: 0.069 inches Fastener Length: Between 0.156 inches and 0.187 inches Head Style: Flat countersunk Head Diameter: Between 0.150 inches and 0.172 inches Head Diameter: Between 0.150 inches and 0.172 inches Locking Feature: Pellet threads Internal Drive Style: Slot Thread Diameter: 0.086 inches Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel Surface Treatment: Cadmium
Thread Direction: Right-hand Thread Length: 0.069 inches Fastener Length: Between 0.156 inches and 0.187 inches Head Style: Flat countersunk Head Diameter: Between 0.150 inches and 0.172 inches Locking Feature: Pellet threads Internal Drive Style: Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel Surface Treatment:
Right-handThread Length:0.069 inchesFastener Length:Between 0.156 inches and 0.187 inchesHead Style:Flat countersunkHead Diameter:Between 0.150 inches and 0.172 inchesLocking Feature:Pellet threadsInternal Drive Style:SlotThread Diameter:0.086 inchesThready Qty Per Inch (tpi):56SlotSlotSlotDuresine Strength (psi):55000 pounds per square inchCountersink Angle:Between 80.0 degrees and 82.0 degreesMaterial:SteelSurface Treatment:SteelSurface Treatment:Steel<
Thread Length: 0.069 inches Fastener Length: Between 0.156 inches and 0.187 inches Head Style: Flat countersunk Head Diameter: Between 0.150 inches and 0.172 inches Locking Feature: Pellet threads Internal Drive Style: Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel Steel Steel
0.069 inches Fastener Length: Between 0.156 inches and 0.187 inches Head Style: Flat countersunk Head Diameter: Between 0.150 inches and 0.172 inches Locking Feature: Pellet threads Internal Drive Style: Slot Thread Diameter: 0.086 inches Thread Diameter: 0.086 inches Stot Stot Stot Stot Stot Stot Stot Sto
Fastener Length:Between 0.156 inches and 0.187 inchesHead Style:Flat countersunkHead Diameter:Between 0.150 inches and 0.172 inchesLocking Feature:Pellet threadsInternal Drive Style:SlotThread Diameter:0.086 inchesThready Qty Per Inch (tpi):56Min. Tensile Strength (psi):55000 pounds per square inchCountersink Angle:Between 80.0 degrees and 82.0 degreesMaterial:SteelSurface Treatment:
Between 0.156 inches and 0.187 inchesHead Style:Flat countersunkHead Diameter:Between 0.150 inches and 0.172 inchesLocking Feature:Pellet threadsInternal Drive Style:SlotThread Diameter:0.086 inchesThready Qty Per Inch (tpi):56Min. Tensile Strength (psi):55000 pounds per square inchCountersink Angle:Between 80.0 degrees and 82.0 degreesMaterial:SteelSurface Treatment:
Head Style:Flat countersunkHead Diameter:Between 0.150 inches and 0.172 inchesLocking Feature:Pellet threadsInternal Drive Style:SlotThread Diameter:0.086 inchesThready Qty Per Inch (tpi):56Min. Tensile Strength (psi):55000 pounds per square inchCountersink Angle:Between 80.0 degrees and 82.0 degreesMaterial:SteelSturface Treatment:
Flat countersunkHead Diameter:Between 0.150 inches and 0.172 inchesLocking Feature:Pellet threadsInternal Drive Style:SlotThread Diameter:0.086 inchesThready Qty Per Inch (tpi):56Min. Tensile Strength (psi):55000 pounds per square inchCountersink Angle:Between 80.0 degrees and 82.0 degreesMaterial:SteelSteelSurface Treatment:
Head Diameter: Between 0.150 inches and 0.172 inches Locking Feature: Pellet threads Internal Drive Style: Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel Steel
Between 0.150 inches and 0.172 inches Locking Feature: Pellet threads Internal Drive Style: Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel Sturface Treatment:
Locking Feature:Pellet threadsInternal Drive Style:SlotThread Diameter:0.086 inchesThready Qty Per Inch (tpi):56Min. Tensile Strength (psi):55000 pounds per square inchCountersink Angle:Between 80.0 degrees and 82.0 degreesMaterial:SteelSteelSurface Treatment:
Pellet threads Internal Drive Style: Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): Chready Qty Per Inch (tpi): So00 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel Steel Surface Treatment:
Internal Drive Style: Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel Steel
Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 76 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel Steel Stuface Treatment:
Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel Steel Surface Treatment:
0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel Steel
Thready Qty Per Inch (tpi):56Min. Tensile Strength (psi):55000 pounds per square inchCountersink Angle:Between 80.0 degrees and 82.0 degreesMaterial:SteelStreatment:
56 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel Surface Treatment:
Min. Tensile Strength (psi):55000 pounds per square inchCountersink Angle:Between 80.0 degrees and 82.0 degreesMaterial:SteelSurface Treatment:
55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel Surface Treatment:
Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel Surface Treatment:
Between 80.0 degrees and 82.0 degrees Material: Steel Surface Treatment:
Material: Steel Surface Treatment:
Steel Surface Treatment:
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 1, cl 3 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0