

NSN 5305-00-004-0374 Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-004-0374 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.399 inches and 0.500 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Hole Diameter:** Between 0.044 inches and 0.050 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi):

180000 pounds per square inch

**Hardness Rating:** 

38.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

155000 pounds per square inch

**Hole Configuration Style:** 

Round internal hexagon

Material:

Steel

**Thread Series Designator:** 

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

## NSN 5305-00-004-0374

Socket Head Cap Screw - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0