NSN 5305-00-004-0380

Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-004-0380

| Thread Class: | |
|---------------------------------------|--|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.282 inches | |
| Fastener Length: | |
| Between 0.344 inches and 0.406 inches | |
| Head Style: | |
| Button | |
| Head Diameter: | |
| 0.375 inches | |
| Head Height: | |
| Between 0.082 inches and 0.092 inches | |
| Locking Feature: | |
| Pellet threads | |
| Internal Drive Style: | |
| Cross recess type 1 | |
| Thread Diameter: | |
| 0.164 inches | |
| Thready Qty Per Inch (tpi): | |
| 32 | |
| Min. Tensile Strength (psi): | |
| 62000 pounds per square inch | |
| Material: | |
| Aluminum alloy | |
| Surface Treatment: | |
| Anodize | |
| Thread Series Designator: | |
| Unc Shelf Life: | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| Demilitarization: | |
| | |
| No | |
| Fiig: A003b0 | |
| | |
| | |