

View Online at <https://aerobasegroup.com/nsn/5305-00-004-2970>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.300 inches and 0.310 inches

Fastener Length:

1.919 inches

Head Style:

Fillister

Head Diameter:

0.562 inches

Head Height:

0.043 inches

Shoulder Diameter:

0.3731 inches first shoulder and 0.3737 inches first shoulder

Shoulder Length:

1.609 inches first shoulder and 1.619 inches first shoulder

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Internal Drive Style:

Slot

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.817 inches first hole and 1.827 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel

Material Specification:

G-1013 fscm 26512 mfr ref single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837 type 2 cl 1 military specification single treatment response or mil-s-5002 military specification single treatment response

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.