NSN 5305-00-004-3159

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-004-3159 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.203 inches and 0.233 inches **Fastener Length:** Between 0.552 inches and 0.572 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.085 inches and 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.339 inches and 0.349 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project Material: Steel comp 304l or steel comp 316l or steel comp 302 or steel comp 347 or steel comp 321 or steel comp 317 or steel comp 316l o comp 310 or steel comp 309 or steel comp 305 or steel comp 304 **Material Specification:** Qq-s-763 300 series cond a federal specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 type 2 federal specification single treatment response **Thread Series Designator:**

Unc

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-00-004-3159

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0