NSN 5305-00-004-3342

Shoulder Screw - Page 1 of 2





Thread Class: 2a **Thread Direction: Right-hand Thread Length:** Between 0.225 inches and 0.280 inches Fastener Length: 0.410 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.335 inches and 0.345 inches **Shoulder Diameter:** 0.178 inches first shoulder Shoulder Length: 0.041 inches first shoulder and 0.077 inches first shoulder **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Hardness Rating: 34.0 rockwell c and 38.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder **Product Name:** Navy special project **Special Features:** With locking element in threads Material: Steel comp 4037 **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 1 cl 2 federal specification single treatment response **Thread Series Designator:**

Unc

NSN 5305-00-004-3342

Shoulder Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

