

View Online at <https://aerobasegroup.com/nsn/5305-00-004-3468>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.366 inches and 0.416 inches

Fastener Length:

Between 0.938 inches and 0.968 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.527 inches and 0.560 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.375 inches

Grip Length:

Between 0.552 inches and 0.572 inches

Thready Qty Per Inch (tpi):

24

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.808 inches first hole and 0.858 inches first hole

Surface Finish:

63.0 microinches grip

Material:

Steel

Material Specification:

H-11 hb0160-001 type 1, fscm 51215 mfr ref single material response

Surface Treatment:

Nickel and zinc

Surface Treatment Specification:

La0109-005, fsc-51215 mfr ref single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0