NSN 5305-00-004-5079

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-004-5079 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.230 inches and 1.270 inches **Fastener Length:** Between 1.980 inches and 2.020 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.480 inches and 0.520 inches **Head Height:** Between 0.540 inches and 0.580 inches **First Diameter From Head:** Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.560 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Point nonstandard no. 6, 0.175 in. Dia, 0.190 in. Lg 90.0 degrees angle Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-004-5079

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.