NSN 5305-00-004-5099

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-004-5099 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.897 inches and 0.971 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.156 inches and 0.172 inches **Locking Feature:** Strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 321 or steel comp 347 or steel comp 302 or steel comp 303 **Material Specification:** Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or mil-s-7720 military specification 3rd material response or astm a582 assn standard 4th material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Data:** 80205-nas662 professional/industrial association standard **Specification Or Standard:** 1 type and 3s style Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-004-5099

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7720 spec.