

NSN 5305-00-004-5326 Assembled Washer Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-004-5326 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.125 inches and 0.157 inches **Fastener Length:** Between 0.218 inches and 0.250 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.072 inches and 0.082 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:**

Primary Washer Outside Diameter:

0.253 inches

Secondary Washer Outside Diameter:

Between 0.253 inches and 0.263 inches

Primary Washer Style:

Split helical ring

Primary Washer Material Thickness:

0.031 inches

Secondary Washer Material Thickness:

Between 0.013 inches and 0.019 inches

Material:

Steel comp 1010

Surface Treatment:

Cadmium and chromate

NSN 5305-00-004-5326

Assembled Washer Screw - Page 2 of 2



Surface	Treatment	Specification:
Suriace	Healineil	Specification.

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Thread Series Designator:

Unc

Specification Data:

80205-nas720 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0