

View Online at <https://aerobasegroup.com/nsn/5305-00-004-5326>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.125 inches and 0.157 inches

Fastener Length:

Between 0.218 inches and 0.250 inches

Head Style:

Pan

Head Diameter:

Between 0.256 inches and 0.270 inches

Head Height:

Between 0.072 inches and 0.082 inches

Washer Quantity:

2

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

55000 pounds per square inch

Secondary Washer Relationship To Primary Washer:

Not identical

Secondary Washer Style:

Flat

Primary Washer Outside Diameter:

0.253 inches

Secondary Washer Outside Diameter:

Between 0.253 inches and 0.263 inches

Primary Washer Style:

Split helical ring

Primary Washer Material Thickness:

0.031 inches

Secondary Washer Material Thickness:

Between 0.013 inches and 0.019 inches

Material:

Steel comp 1010

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Thread Series Designator:

Unc

Specification Data:

80205-nas720 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0