## NSN 5305-00-004-7175

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-004-7175 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.349 inches and 0.416 inches **Fastener Length:** Between 0.859 inches and 0.906 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.578 inches and 0.611 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Countersink Angle:** Between 99.5 degrees and 100.5 degrees **Surface Finish:** 32.0 microinches grip Material: Steel comp 4140 or steel comp 8740 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** 11-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-004-7175

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0