Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-004-7194

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.357 inches and 0.397 inches	
Fastener Length:	
Between 0.720 inches and 0.750 inches	
Head Style:	
Pan	
Head Diameter:	
Between 0.306 inches and 0.322 inches	
Head Height:	
Between 0.105 inches and 0.115 inches	
First Diameter From Head:	
Between 0.120 inches and 0.130 inches	
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	
Between 0.353 inches and 0.363 inches	
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.164 inches	
Thready Qty Per Inch (tpi):	
32	
Externally Relieved Body Diameter Quantity:	
1	
Material:	
Stainless steel	
Material Specification:	
Astma582, ty303, conda assn standard single material response	
Surface Treatment:	
Passivate	
Surface Treatment Specification:	
Mil-f-14072 military specification single treatment response	
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Externally Relieved Body Screw - Page 2 of 2



Fiig: A003b0 Mil-std (military Standard):

Mil-f-14072 spec.