Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-004-9187

2a Thread Direction: Right-hand Thread Length: 0.679 inches Fastener Length: Between 0.740 inches and 0.770 inches Head Style: Flat chamfer Head Diameter: 0.375 inches Head Height: 0.375 inches Head Height: 0.375 inches Head Height: 0.375 inches Head Height: 0.250 inches Locking Feature: Pellet threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material Specification: Qr-s-763 federal specification single material response Surface Treatment: Passivate	Thread Class:
Thread Direction: Right-hand Thread Length: 0.679 inches Fastener Length: Between 0.740 inches and 0.770 inches Head Style: Flat chamfer Head Diameter: 0.375 inches Head Height: 0.375 inches Head Height: 0.375 inches Head Height: 0.250 inches Locking Feature: Pellet threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches Vidth Across Flats: 0.250 inches Mitch Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Material Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	
Right-handRight-handThread Length:0.679 inchesFastener Length:Between 0.740 inches and 0.770 inchesHead Style:Flat chamferHead Diameter:0.375 inchesHead Height:0.250 inchesLocking Feature:Pellet threadsInternal Drive Style:HexagonThread Diameter:0.250 inchesUdth Across Flats:0.188 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):125000 pounds per square inchMaterial:Stainless steelMaterial Specification:Qq-s-763 federal specification single material responseSurface Treatment:Passivate	
Thread Length: 0.679 inches Fastener Length: Between 0.740 inches and 0.770 inches Head Style: Flat chamfer Head Diameter: 0.375 inches Head Height: 0.250 inches Locking Feature: Pellet threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	
0.679 inches Fastener Length: Between 0.740 inches and 0.770 inches Head Style: Flat chamfer Head Diameter: 0.375 inches Head Height: 0.375 inches Head Height: 0.375 inches Head Height: 0.250 inches Locking Feature: Pellet threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches Vidth Across Flats: 0.250 inches Vidth Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	
Fastener Length:Between 0.740 inches and 0.770 inchesHead Style:Flat chamferHead Diameter:0.375 inchesHead Height:0.375 inchesLocking Feature:Pollet threadsInternal Drive Style:HexagonThread Diameter:0.250 inchesUoth Across Flats:0.188 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):125000 pounds per square inchMaterial:Stainless steelMaterial Specification single material responseCurface Treatment:Passivate	-
Between 0.740 inches and 0.770 inches Head Style: Flat chamfer Head Diameter: 0.375 inches Head Height: 0.375 inches Head Height: 0.250 inches Locking Feature: Pellet threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches Vidth Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material Specification single material response Surface Treatment: Passivate	
Head Style:Flat chamferHead Diameter:0.375 inchesHead Height:0.250 inchesLocking Feature:Pellet threadsInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:0.188 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):125000 pounds per square inchMaterial:Stainless steelMaterial Specification:Qays-763 federal specification single material responseSurface Treatment:Passivate	-
Flat chamferHead Diameter:0.375 inchesHead Height:0.250 inchesLocking Feature:Pellet threadsInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:0.188 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):125000 pounds per square inchMaterial:Stainless steelMaterial Specification single material responseSurface Treatment:Passivate	
Head Diameter:0.375 inchesHead Height:0.250 inchesLocking Feature:Pellet threadsInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:0.188 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):125000 pounds per square inchMaterial:Stainless steelMaterial Specification single material responseSurface Treatment:Passivate	Head Style:
0.375 inches Head Height: 0.250 inches Locking Feature: Pellet threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches Vidth Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	Flat chamfer
Head Height:0.250 inchesLocking Feature:Pellet threadsInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:0.188 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):125000 pounds per square inchMaterial:Stainless steelMaterial Specification:Qq-s-763 federal specification single material responseSurface Treatment:Passivate	Head Diameter:
0.250 inches Locking Feature: Pellet threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches Vidth Across Flats: 0.250 inches Vidth Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	0.375 inches
Locking Feature: Pellet threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	Head Height:
Pellet threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	0.250 inches
Internal Drive Style: Hexagon Thread Diameter: 0.250 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	Locking Feature:
Hexagon Thread Diameter: 0.250 inches Width Across Flats: 0.188 inches 0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material: Qq-s-763 federal specification single material response Surface Treatment: Passivate	Pellet threads
Thread Diameter: 0.250 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	Internal Drive Style:
0.250 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	Hexagon
 Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate 	Thread Diameter:
0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	0.250 inches
Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	Width Across Flats:
28 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	0.188 inches
Min. Tensile Strength (psi): 125000 pounds per square inch Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	Thready Qty Per Inch (tpi):
125000 pounds per square inch Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	28
Material:Stainless steelMaterial Specification:Qq-s-763 federal specification single material responseSurface Treatment:Passivate	Min. Tensile Strength (psi):
Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	125000 pounds per square inch
Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate	Material:
Qq-s-763 federal specification single material response Surface Treatment: Passivate	Stainless steel
Surface Treatment: Passivate	Material Specification:
Surface Treatment: Passivate	Qq-s-763 federal specification single material response
Surface Treatment Specification:	Passivate
	Surface Treatment Specification:
-	-
	-
-	
Unf	
Unf Shelf Life:	
Unf Shelf Life: N/a	
Unf Shelf Life: N/a Unit Of Measure:	
Unf Shelf Life: N/a Unit Of Measure:	
Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	
-	Surface Treatment Specification:
Qq-p-35 federal specification single treatment response	Qq-p-35 federal specification single treatment response
Thread Series Designator:	Thread Series Designator:
	-
-	
Unf	Shelf Life:
Unf	N/a
Unf Shelf Life:	Unit Of Measure:
Unf Shelf Life: N/a	
Unf Shelf Life: N/a Unit Of Measure:	Demilitarization:
Unf Shelf Life: N/a Unit Of Measure:	Νο
Unf Shelf Life: N/a Unit Of Measure:	

NSN 5305-00-004-9187

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

