NSN 5305-00-005-0040

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-005-0040 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.360 inches **Fastener Length:** 0.600 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** Between 0.098 inches and 0.102 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.140 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 **Material Specification:** 66 federal standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-005-0040

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0