NSN 5305-00-005-0450

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-005-0450 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.290 inches and 0.300 inches **Fastener Length:** Between 0.720 inches and 0.730 inches **Head Style:** Hexagon **Head Height:** Between 0.070 inches and 0.080 inches Width Between Flats: Between 0.307 inches and 0.317 inches **First Diameter From Head:** Between 0.089 inches and 0.092 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.420 inches and 0.440 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-005-0450

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0