

View Online at <https://aerobasegroup.com/nsn/5305-00-005-0465>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.366 inches and 0.416 inches

Fastener Length:

Between 0.938 inches and 0.968 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.552 inches and 0.563 inches

Head Height:

Between 0.191 inches and 0.215 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Single Shear Strength:

17250 pounds per square inch

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.375 inches

Grip Length:

Between 0.552 inches and 0.572 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

260000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.808 inches first hole and 0.858 inches first hole

Special Features:

Recess painted with aluminum silicone na2-1315 type 2 43999

Material:

Steel

Material Specification:

Hb0160-001 type 2 h-11, fscm 43999 mfr ref single material response

Surface Treatment:

Nickel and zinc

Surface Treatment Specification:

La0109-005, fscm 43999 mfr ref single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0