NSN 5305-00-005-0621



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-005-0621 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** Between 1.636 inches and 1.683 inches **Head Style:** Pan **Head Diameter:** Between 0.361 inches and 0.381 inches **Head Height:** Between 0.103 inches and 0.118 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.192 inches **Grip Length:** Between 1.360 inches and 1.390 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch **Surface Finish:** 32.0 microinches grip Material: Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:**

Unjf

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-00-005-0621

Close Tolerance Screw - Page 2 of 2



Demi			

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.