NSN 5305-00-005-1533

Shoulder Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-005-1533



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.293 inches and 0.310 inches Fastener Length: Between 0.852 inches and 0.878 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.357 inches and 0.375 inches **Head Height:** Between 0.182 inches and 0.188 inches **Shoulder Diameter:** 0.247 inches first shoulder and 0.248 inches first shoulder Shoulder Length: 0.497 inches first shoulder and 0.503 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.125 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Shoulder Shape: Round first shoulder **Special Features:** Patch type element on thread Material: Steel **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure:

NSN 5305-00-005-1533

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

