NSN 5305-00-005-8193

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-005-8193 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.309 inches and 0.329 inches **Fastener Length:** Between 0.495 inches and 0.505 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.234 inches and 0.244 inches **Head Height:** Between 0.108 inches and 0.118 inches **First Diameter From Head:** Between 0.097 inches and 0.101 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.176 inches and 0.186 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 **Material Specification:** 66 federal standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 1 type Shelf Life:

N/a

NSN 5305-00-005-8193

Externally Relieved Body Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0