Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-005-8210



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.198 inches and 0.266 inches

Fastener Length:

Between 0.234 inches and 0.266 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.154 inches and 0.163 inches

Head Height:

Between 0.095 inches and 0.099 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.099 inches

Width Across Flats:

Between 0.078 inches and 0.479 inches

Thready Qty Per Inch (tpi):

56

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-005-8210

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

