NSN 5305-00-005-8245

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-005-8245 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.186 inches and 0.264 inches **Fastener Length:** Between 0.292 inches and 0.312 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.067 inches and 0.083 inches Washer Quantity: **Internal Drive Style:** Cross recess type ia **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** Between 0.195 inches and 0.208 inches **Secondary Washer Outside Diameter:** Between 0.245 inches and 0.250 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.031 inches **Secondary Washer Material Thickness:** Between 0.017 inches and 0.025 inches Material: Copper alloy 360 or copper alloy **Surface Treatment:** Nickel **Thread Series Designator:** Unc

NSN 5305-00-005-8245

Assembled Washer Screw - Page 2 of 2



_			-		
C	hο	14		.ife	
•			_	.II C	-

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0