

View Online at <https://aerobasegroup.com/nsn/5305-00-005-8292>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.141 inches and 0.171 inches

**Fastener Length:**

Between 0.490 inches and 0.510 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.256 inches and 0.270 inches

**Head Height:**

Between 0.087 inches and 0.097 inches

**First Diameter From Head:**

Between 0.081 inches and 0.091 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.339 inches and 0.349 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Product Name:**

Navy special project

**Material:**

Steel comp 304l or steel comp 316l or steel comp 302 or steel comp 347 or steel comp 321 or steel comp 317 or steel comp 316 or steel comp 310 or steel comp 309 or steel comp 305 or steel comp 304

**Material Specification:**

Qq-s-763 federal specification all material responses

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924 cl 4 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.